




Leading - edge Technology

- ▶ Maximum efficiency of 97% and wide input voltage range
- ▶ Internal DC switch
- ▶ Transformerless GT topology
- ▶ Compact design
- ▶ Ethernet / RF technology / Wi-Fi
- ▶ Sound control
- ▶ Easy installation
- ▶ Comprehensive Growatt warranty program

1.5k efficiency



GROWATT NEW ENERGY TECHNOLOGY Co.,LTD

A: No.28 Guanghai Road, Longteng Community, Shiyan, Baoan District, Shenzhen, P.R.China.

T: + 86 755 2747 1900 F: + 86 755 2749 1460 E: info@ginverter.com

	Growatt 1000S	Growatt 1500S
Input Data		
Max. DC power	1300W	1800W
Max. DC voltage	450V	450V
Start voltage	90V	150V
PV voltage range	70V - 450V	100V - 450V
MPPT work voltage range/ nominal voltage	70V-450V/180V	120V-450V/250V
Full load dc voltage range	110V - 400V	175V - 450V
Number of MPP trackers /strings per MPP tracker	1 / 1	1 / 1
Max. input current /per string	10A/10A	10A/10A
Output (AC)		
Rated AC output power	1000W	1600W
Max. AC power	1100W	1650W
Max. output current	5.5A	8A
AC nominal voltage; range	220V,230V,240V; 180Vac-280Vac	220V,230V,240V; 180Vac-280Vac
AC grid frequency ;range	50Hz, 60Hz; ± 5Hz	50Hz, 60Hz; ± 5Hz
Power factor	1	1
THDI	<3%	<3%
AC connection	Single phase	Single phase
Efficiency		
Max. efficiency	97%	97%
Euro-eta	95.5%	96.5%
MPPT efficiency	99.5%	99.5%
Protection Devices		
DC reverse polarity protection	yes	yes
DC switch rating for each MPPT	yes	yes
Output over current protection	yes	yes
Output overvoltage protection-varistor	yes	yes
Ground fault monitoring	yes	yes
Grid monitoring	yes	yes
Integrated all-pole sensitive leakage current monitoring unit	yes	yes
General Data		
Dimensions (W / H / D) in mm	271*267*127mm	271*267*127mm
Weight	4.7Kg	4.7Kg
Operating temperature range	-25 °C ... +60 °C	-25 °C ... +60 °C
Noise emission (typical)	≤25 dB(A)	≤25 dB(A)
Self-Consumption night	< 0.5 W	< 0.5 W
Topology	Transformerless	Transformerless
Cooling concept	Natural	Natural
Environmental Protection Rating	IP 65	IP 65
Altitude	2000m without derating	2000m without derating
Relative Humidity	0~95%	0~95%
Features		
DC connection	H4/MC4(opt)	H4/MC4(opt)
AC connection	Connector	Connector
Display	LCD	LCD
Interfaces: RS232/Wi-Fi/ Ethernet /RF	yes / opt / opt / opt	yes / opt / opt / opt
Warranty: 5 years / 10 years	yes / opt	yes / opt
Certificates and Approvals		