



General

MagnetPaint is for use on primed plaster, wallboard, wood, and primed plastics or glass. MagnetPaint is a dark grey latex dispersion-primer, containing rustfree iron particles on which magnets stick.

Awarded European safety norm for childrens toys: EN 71-3.

Surface preparation

Remove all surface contamination. Surface should be dry, clean, grease-proof and smooth. Sand glossy surfaces dull. Use primer for optimal result.

Application

Apply as a primer under blackboardpaint, wallpaint, wallpaper or laquer. Multiple coats increase magnetic strength. 3 Coats are advised (500 – 800 micron) for common use. The combination of coat thickness and quality/type of magnets determine the magnetic strength.

Tools

Brush, roller, spray-gun (max. +5% water)

Charasteristics (at 20 °C and 70 RH)

Appearance	Dull
Colour:	Dark grey
Density:	2,62 g / L.
Coverage:	Depends on surface (preparation) and application method around 6 m ² /L
Viscosity:	Ready for use
VOC:	0 g / L.
Room temperature:	>10°C
Dry to the touch:	After approx. 10 minutes
Extra coats	After approx. 4 hours
Topcoat:	After approx. 24 hours.
Volumes:	250, 500, 1000, 2500, 5000 ml. and bulk
Shelf life:	Minimum of 6 months at a temperature between 5 and 20°C in, unopened, original packaging.

Safety

See: Material Safety Data Sheet