

NSEX-160R

Rechargeable Atex Zone 1 • 2 Flashlight



Front Spot Light



Rear Torch Light



Key features:

- Intrinsically safe LED Flash Light for use in Zone 1 • 2 • 21 • 22 hazardous areas
- Front spot light + Rear torch light, High/Low/Strobe light modes
- Explosion proof
- High powered OSRAM LED
- Charging time: 6hrs
- Running time: High: 9hrs | Low: 18hrs
- Battery: 2.2Ah Lithium-ion
- Secure grip, high strength aluminium housing
- Easy to use, maintenance free



INTRINSICALLY SAFE LED FLASH LIGHT FOR USE IN ZONE 1 • 2 • 21 • 22 HAZARDOUS AREA


RoHS  



Certifications and Ratings:

- CLASS I DIV 1&2 GRP ABCD
- CLASS II DIV 1 GRP EFG,
- CLASS II DIV 2 GRP FG
- CLASS III DIV 1, CLASS III DIV 2
- Ex ib IIC T4 Gb
- Ex tb IIIC T130°C Db IP68
- ATEX ZONE 1 & 21 | ZONE 2 & 22
- ATEX Certificate No.: TÜV 15 ATEX 7713X
- Rohs
- CE
- IP68 (3M)

Typical applications include Fire Fighters, Public Security, Gas station, manufacturing plants, chemical and petrochemical processing facilities.



PRODUCT CODE	DIMENSIONS
NSEX160R	(L)156x(w)35mm

