

## Z-Ultimate® 3000T White

# Permanent labels

## Thermal Transfer

### Description

A top coated white gloss polyester thermal transfer label stock with excellent print quality. Coated specially for use with Zebra 5095 resin thermal transfer ribbon to produce outstanding print quality and image durability. High-strength acrylic adhesive offers superior strength and adhesion for a wide variety of surfaces. Unparalleled smear/scratch resistance for a thermal transfer label.

Note: Z-Ultimate 3000T White is not to be used for fanfold applications.

### Suggested Applications

- Shelf or scan-pallet labels.
- Labels exposed to acid or alkali solutions; top side printed circuit board applications
- Water-immersed labels.
- Labels in contact with moving parts or friction conveyor drives
- On site, on-demand printing of UL Type R Listing marks/ CSA compliant labelling e.g. rating plates
- Asset tracking labels

### Technical Specifications

	Description	Caliper
Facestock	White pearlescent coated polyester	50 microns
Adhesive	Permanent acrylic based adhesive	23 microns
Liner	65gsm White Glassine Liner	56 microns
		Total 126 microns

**Recommended Zebra printers:** desktop, mid-range and high-performance thermal transfer printers

**Recommended Zebra ribbons:** 4800, 5095, 5100

**Minimum application temperature:** 10°C

**Service temperature range:** -40°C to 150°C

**Recommended storage conditions:** One year duration when stored at approx 20C at 50% RH

