



## STARTRONIC 330 230V



### Overview

#### STARTRONIC 330 230V

cod. 829033

Digital, microprocessor controlled battery charger, maintainer and starter for charging all types of batteries (GEL/AGM/START-STOP), with 6/12/24V voltage and starting of cars, vans and trucks. Startronic protects the on-board electronic such as ABS, airbag, electronic injection, etc. Running modes: TEST, CHARGE, TRONIC, START and STAND-BY. The STAND-BY function is activated through connection to the cigarette lighter outlet of the car, it allows to disconnect and charge the car battery without erasing the preset values of the on-board computer. The TRONIC function allows for the electronic control of charging current, automatic interruption and restart. The new implemented technology SAFE START does not damage the on-board electronics during the starting phase (START) because it eliminates the overvoltages typical of the traditional starters. Characteristics: choice of charge current 1÷30A \* display to check battery voltage, charging current and time \* display to check battery status \* protection against reverse polarity, battery failure, thermostatic interruption, faulty battery charger.



1 PH 230V



FAN COOLED



MICROPROCESSOR



MOTORCYCLE



CAR



BOAT



VAN



CE MARKING



EAC CERTIFICATION

### Technical data



CODE 829033



MAINS VOLTAGE 230 - 1 ph V50/60Hz



CHARGE/START POWER 1,1 / 7 kW



CHARGING VOLTAGE 6 / 12 / 24 V



CURRENT RANGE 1 - 30 A



EFFECTIVE CHARGING CURRENT 50 A



## STARTRONIC 330 230V

RATED CHARGE CURR. EN60335-2-29 30 A	START CURRENT 1V/C EN60335-2-29 210 A	MAX STARTING CURRENT 230 A
MIN./MAX RATED REFERENCE CAPACITY 10 / 450 Ah	DIMENSIONS 39 - 26 - 23 cm(L,W,H)	WEIGHT 16,3 kg
EAN CODE 800489771273 4	PIECES/PALLET 18 pz/pallet	PIECES/PALLET - B 12 pz/pallet - B

### Included Accessories



CABLE 6 MMQ 1,8 M - 120300



COLORADO 150B WORK CLAMP 150A - 712001



COLORADO 150R POSITIVE CLAMP 150A - 712002

LIGHTER CONNECTION CABLE - 120948