

DESCALING TABLETS

Descaling tablets are designed to efficiently and safely descale espresso machines with water tanks and other coffee brewing equipment. The descaling process (also known as decalcifying and de-kalking) removes hard water scale from the boiler or thermoblock and the group head or coffee brewer.



FEATURES & BENEFITS


- Quick dissolution time
- Rapid descaling action
- Non-corrosive formulation that is safe to espresso machine and coffee brewing equipment
- Accurate dosing

RECOMMENDED FOR

All espresso machines and coffee brewers with water tanks and pour-over brewers with rapid heat thermo-blocks.

INSTRUCTIONS

Follow machine manufacturer's maintenance instructions. Always rinse with fresh water after cleaning.



AVAILABLE IN

Product	Type of unit pack	Tablet weight	# tablets per unit	# of units per case	# of tablets per case	Product code/individual	Product code/carton
Descaling Tablets	Blister	18g	9	9	81	E26990	E25598

CERTIFICATIONS

Cafetto is Quality Endorsed to ISO9001:2008
Cafetto's manufacturing facility is HACCP and GMP certified.

ESPRESSO MACHINES WITH WATER TANKS

Fill a clean container of at least 1.25 litres (42oz) capacity with 1 litre (35oz) of cold or warm (not hot) water. Following the guide below place the required number of Cafetto® Descaling Tablets in the filled container.

Frequency → Hardness ↓	Monthly	3 monthly	6 monthly	Annually
Soft	Not required	Not required	1 tablet	2 tablets
Moderate	Not required	1 tablet	2 tablets	3 tablets
Hard	1 tablet	2 tablets	3 tablets	4 tablets

Empty the machine's water tank.

When the tablets have completely dissolved (which will take a few minutes – warm water speed the dissolution) pour the solution into the water tank. Follow the machine's descaling instructions.

If no instructions are available, turn the machine's power on and put empty containers under the brewing group and the steam wand. Operate the brewing cycle until solution comes out of the brewing group for about one minute, then stop the pump. Open the steam valve and when solution comes out of the wand for one minute and then shut the valve. Wait five minutes and then repeat the process.

Keep repeating this step until there is no flow from either the brewing group or the steam wand.

Rinse the water tank and fill with fresh water. Run the water through both the brewing group and the steam wand until the tank is empty.

Refill the water tank with fresh water and the machine is ready for use.

COFFEE BREWERS

Fill a clean container of at least 1.25 litres (42oz) capacity with 1 litre (35oz) of cold or warm (not hot) water. Following the guide below place the required number of Cafetto® Descaling Tablets in the filled container.

Frequency → Hardness ↓	Monthly	3 monthly	6 monthly	Annually
Soft	Not required	Not required	1 tablet	2 tablets
Moderate	Not required	1 tablet	2 tablets	3 tablets
Hard	1 tablet	2 tablets	3 tablets	4 tablets

Insert the filter funnel without paper into its normal position with the empty coffee air-pot in position to capture the descaling solution. Turn the brewer on and pour the descaling solution into the cold water chamber. Allow the entire contents flow into the air-pot to descale the system.

Empty the air-pot and reposition under the brewer. Rinse the container used to dissolve the tablets, fill with 1 litre (35oz) of fresh water and pour into the brewer reservoir with the brewer switched on. Allow the water to pour completely through the filter funnel into the air-pot to rinse the system.

Empty and thoroughly rinse the air-pot in fresh water and rinse the filter funnel. Re-position the filter funnel and air-pot in the brewer and the descaling process is complete.