



TECHNICAL DATA SHEET



High Performance Cast PVC film

3D Formable Ultra Flexible Wrap Vinyl

W-series - multilayered cast - repositionable adhesive with air channels (AX™ 2.0 system)

APPLICATIONS

Long-term high performance CAST film with outstanding dimensional stability and good conformability for applications onto flat surfaces and moderate curves, with or without rivets designed for full and partial vehicle wraps.

This exclusive CAST product combines speedy and trouble free film application, thanks to the AX airchannel liner which allows air to be easily squeezed out during the application and the permanent repositionable adhesive that thanks to the low initial tack allows an easy repositioning during application. The final strong bond ensure a secure and weatherproof finish.

After application, all edges and stretched areas must be heat-set(post heated) at 100-105°C.

This film is available in 1.52 m (60") wide roll.

APPLICATION

Substrate Preparation: All surfaces to which the material will be applied must be thoroughly cleaned with SOTT SC-02 SurfaceCleaner. Ensure all traces of any contamination and cleaning agents are totally removed prior to application of the material.

Self-adhesive media should only be applied to OEM painted surfaces and their use on repaired or damaged paintwork is not recommended.

The compatibility of lacquers and paints should be tested by the user prior to the application.

Please refer to our Application Guidelines for specific technical details for the correct application and removal of the media.

Maintenance & Cleaning: Recommended a manual washing with non abrasive cleaner. Use SOTT Cleaners. Suggested the use mild soap and sponge, avoid to hit the edge to avoid edge lifting.

SHELF LIFE

24 months, applicable only to the material delivered by SOTT which has not undergone further processing, under the following STORAGE CONDITIONS: This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity. Storage area must be dry and clean. Keep the material in the original packaging when not used in order to protect it from dust and contamination. Do not expose to direct sunlight or heat source.

Face Material

Type	Cast vinyl film
Colour and Finish	Gloss, Matte, Metallic, Pearl and Satin
Weight	114 g/m ² ± 10% -ISO-536
Thickness	100-140 µ (4-5.2 mil) ± 10% -ISO 534-80
Shrinkage	< 1 %
Tensile Strength along	14 N/mm ²
Tensile Strength across	13 N/mm ²
Elongation at break along	90 %
Elongation at break across	95 %
Outdoor vertical exposure durability*	48 months
Outdoor horizontal exposure durability*	24 months

Adhesive

Solvent based repositionable permanent grey adhesive, featuring low initial tack with high final adhesion value, good water resistance. Specially designed for wrapping objects with flat and smooth surfaces.

Reference:	SOTT-AX44RPS
Type	Repositionable permanent
Min. Appl. Temp.	+10°C
Service Temp.	-20°C/+120°C
Shear	Very high
Tack	>3 N/25mm FINAT FTM9
Final Adhesion	>15 N/25mm FINAT FTM2

Liner

Type	Airflow pattern-double sided PE coated kraft paper
Colour and Finish	White Weight 135 g/m ² ± 10% PP-032 - ISO 536
Thickness	150 micron ± 10% ISO 534
Transparency	n.a. % DIN 53 147-64

*Please read our Product Guideline sheet

CONDITIONS OF SALE

The following is made in lieu of all warranties expressed or implied:

All statements, technical information and recommendations published by SOTT relating to ULTIMATE PREMIUMPLUS™ products are based on tests believed to be reliable and within the accuracy of the equipment used to obtain the specific values. Their accuracy or completeness is not guaranteed and SOTT makes no warranty with regard thereto. Seller's and manufacturer's only responsibility shall be to replace any quantity of the product proved defective. Seller and manufacturer shall not be liable for injury, loss or damage, direct or consequential, arising out of use or the inability to use the product. Nor shall seller or manufacturer be liable for any costs or expenses incurred in the processing or printing on the product. Before using, user shall determine the suitability of the product for its intended use, User assumes all risk and liability of every nature in connection therewith. No statements or recommendations other than those contained in the technical information published by SOTT shall have force or effect unless contained in an agreement manually signed by the officers of seller and manufacturer.

