

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : 600-TRL 1000 folieverwijderaar
 Type of product : Detergent

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only
 Industrial
 Use of the substance/mixture : Cleaning liquid for removing foil.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

SOTT INTERNATIONAL BV
 De Donge 2c
 5684 PX Best - Nederland
 T +31(0)499-751810
info@sott-international.com - www.sott-international.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number
IRELAND (REPUBLIC OF)	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2166 (public, 8am - 10pm, 7/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225
 Eye Irrit. 2 H319
 STOT SE 3 H336

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11
 Xi; R36
 R66
 R67

Full text of R-phrases: see section 16

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazardous ingredients :

butanone

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapour
 H319 - Causes serious eye irritation
 H336 - May cause drowsiness or dizziness

Precautionary statements (CLP) :

P280 - Wear tight fitting safety glasses
 P337+P313 - If eye irritation persists: Get medical advice/attention

600-TRL 1000 folieverwijderaar

Safety Data Sheet

according to Regulation (EC) No. 453/2010

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P233 - Keep container tightly closed
P314 - Get medical advice/attention if you feel unwell

EUH phrases : EUH066 - Repeated exposure may cause skin dryness or cracking

2.3. Other hazards

Adverse physicochemical, human health and environmental effects : Highly flammable liquid and vapour. May cause drowsiness or dizziness. Causes serious eye irritation.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butanone	(CAS No) 78-93-3 (EC no) 201-159-0 (EC index no) 606-002-00-3 (REACH-no) 01-2119457290-43	>= 50	F; R11 Xi; R36 R66 R67	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
silicon dioxide, chemically prepared substance with national workplace exposure limit(s) (IE)	(CAS No) 7631-86-9 (EC no) 231-545-4 (REACH-no) 01-2119379499-16	10 - 25	Not classified	Not classified

Full text of R- and H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : May cause drowsiness or dizziness.
Symptoms/injuries after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Carbon dioxide. Dry powder. Foam.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

600-TRL 1000 folieverwijderaar

Safety Data Sheet

according to Regulation (EC) No. 453/2010

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.
- Incompatible materials : Reacts violently with (strong) oxidizers.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

silicon dioxide, chemically prepared (7631-86-9)		
Ireland	Silica amorphous, dust (inhalable dust, OEL (8 hours ref)): 6 mg/m ³ Silica amorphous, dust (respirable dust, OEL (15 min ref)): 2,4 mg/m ³	
butanone (78-93-3)		
EU	Local name	Butanone
EU	IOELV TWA (mg/m ³)	600 mg/m ³
EU	IOELV TWA (ppm)	200 ppm
EU	IOELV STEL (mg/m ³)	900 mg/m ³
EU	IOELV STEL (ppm)	300 ppm
Ireland	Local name	Methyl ethyl ketone (MEK)
Ireland	OEL (8 hours ref) (mg/m ³)	600 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	200 ppm
Ireland	OEL (15 min ref) (mg/m ³)	900 mg/m ³
Ireland	OEL (15 min ref) (ppm)	300 ppm
Ireland	Notes (IE)	Sk,IOELV

8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Hand protection : Butyl rubber gloves
- Eye protection : tight fitting safety glasses
- Skin and body protection : Wear suitable protective clothing
- Respiratory protection : Provide local exhaust or general room ventilation to minimize mist and/or vapour concentrations. Gas mask with filter type A. When operating in, e.g., confined space or with large quantities: respiratory protection
- Environmental exposure controls : Avoid release to the environment.
- Other information : Do not eat, drink or smoke during use.

600-TRL 1000 folieverwijderaar

Safety Data Sheet

according to Regulation (EC) No. 453/2010

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous.
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
pH solution	: 6,0 (10 g/l)
Relative evaporation rate (butylacetate = 1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 80 °C
Flash point	: -4 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour Pressure 20°C	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0,85
Density	: 0,85 kg/l
Solubility	: partly miscible.
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour. Under fire conditions, hazardous fumes will be present.

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

butanone (78-93-3)	
LD50 oral rat	3400 mg/kg
LD50 dermal rabbit	13000 mg/kg

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Causes serious eye irritation.

600-TRL 1000 folieverwijderaar

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

butanone (78-93-3)

LC50 fish 1	3220 mg/l 96h
-------------	---------------

12.2. Persistence and degradability

butanone (78-93-3)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

12.3. Bioaccumulative potential

butanone (78-93-3)

Bioconcentration factor (BCF REACH)	3 (calculated value)
-------------------------------------	----------------------

Log Pow	0,3
---------	-----

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.

SECTION 14: Transport information

In accordance with ADR

14.1. UN number

UN-No. (ADR) : 1193

14.2. UN proper shipping name

Proper Shipping Name (ADR) : ETHYL METHYL KETONE (METHYL ETHYL KETONE)

Transport document description (ADR) : UN 1193 ETHYL METHYL KETONE (METHYL ETHYL KETONE), 3, II, (D/E)

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3

Danger labels (ADR) : 3



14.4. Packing group

Packing group (ADR) : II

600-TRL 1000 folieverwijderaar

Safety Data Sheet

according to Regulation (EC) No. 453/2010

14.5. Environmental hazards

Dangerous for the environment : No
Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : F1
Hazard identification number (Kemler No.) : 33
Orange plates :



Tunnel restriction code (ADR) : D/E

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	butanone, ethyl methyl ketone
3.a. Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	butanone, ethyl methyl ketone
3.b. Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	butanone, ethyl methyl ketone
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	butanone, ethyl methyl ketone

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out for the substance or the mixture by the supplier

SECTION 16: Other information

Full text of R-, H- and EUH-phrases:

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
EUH066	Repeated exposure may cause skin dryness or cracking
R11	Highly flammable
R36	Irritating to eyes
R66	Repeated exposure may cause skin dryness or cracking
R67	Vapours may cause drowsiness and dizziness
F	Highly flammable
Xi	Irritant

600-TRL 1000 folieverwijderaar

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Safety Data Sheet applicable for regions : EU; IE

SDS EU (REACH Annex II) - SOTT

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product